

In the SPECIFICATIONS section of the application

- 1) First sentence in paragraph four (4) had the words “drawers or any similar four sided assembly” added.
- 2) The last sentence in Paragraph 4 (Cardboard or paper can be placed over the fixtures to prevent excess glue from getting on the fixtures.) was separated into paragraph 5 for clarity

In the BACKGROUND section of the Application

- split 1) The first paragraph was split into two paragraphs and a fourth paragraph was added. These changes were made for clarity purposes. The first paragraph was approximately in the middle after the sixth sentence and the words”parallel opposing surfaces.”

- 2) The first two sentences of the new second paragraph were changed as follows:

From:

However, these clamping devices cannot hold the work pieces or other articles in a square position that is often required. For example, to grip the corner of picture frames specialty configured miter jigs having mitered gripping surfaces have been designed.

To:

At the present time, clamping devices cannot hold the work pieces or other articles in a square position that is often required. For example, to grip the corner of picture frames, drawers or other similar assemblies special configured miter jigs having mitered gripping surfaces have been designed.

- 3) The fourth paragraph that was added is as follows:
The present invention provides the versatility of not requiring to be attached to a special jig but can be used on different bar clamps. It can also maintain the assembly in a square, level fashion as the Bar Clamp Corner Squaring Fixture has a bottom which allows the pieces to rest on them while they are being assembled.

In the SUMMARY OF THE INVENTION section of the application

Negative references to current devices have been removed from the Third paragraph.

The following words have been deleted:

... which current devices are not capable of doing because they are attached to the jaws on the beam clamping devices which are inherently loose and do not provide a support on the base like the Bar Clamp Corner Squaring Fixture.

And replace with:

This is an important requirement when attempting to assemble parts cut at 45 degrees. If the parts are not maintained in a level position the corners will “open” and will not provide a professional appearance. The Bar Clamp Corner Squaring Fixture is capable of keeping the corners square and level because they are nested in the jaws on the beam clamping devices which apply pressure to each device and the Bar Clamp Corner Squaring Fixture provides a support for the assembly that is being put together.

In the DESCRIPTION OF DRAWINGS section of the application.

1) Description of Figure 1A - Second sentence was changed

From:

Provided dimensional information for the adaptors

To:

The dimensional information for the adaptor is also provided in three (3) separate views of the adaptor.

2) Description of Figure 2A – Sentence is changed

From:

Shows all four adaptors in place and how they would be clamped with four beam clamp assemblies.

To:

Shows all four adaptors in place and how they would clamp a picture frame with four beam clamp assemblies